

FP2 28V (24V)/2000W



Switched power supply FlatPack 2 28V (24V)/2000W with two fans with variable speed according to the temperature.

Rating: Not Rated Yet

Price:

Sales price without tax: 249,00 €

[Ask a question about this product](#)

Description

- **Type of source:** AC / DC
- **Series:** FP2
- **Input:** 85 ~ 290AC 44-66Hz
- **Max. Input Current:** 13A_{RMS} at 250V/50Hz
- **Max. lead to ground:** 2.0m at 250V/50Hz
- **Power Factor:** > 0.99 at 50% and higher burden
- **Input protection:** varistor surge, a fuse, disconnect the overvoltage (> 290VAC)
- **Output:** 21-29VDC 84.0 (26.7VDC nominal)
- **Power:** 2000W
- **Stabilize current:** + / - 5% at 10-100% load
- **Static voltage regulation:** + / - 5% at 10-100% load
- **Dynamic voltage regulation:** + / - 5% at 10-90% and 90-10% load regulation time <50 ms
- **Output hold time:** > 20ms at 1000W 21VDC and outlet
- **Noise and spurious voltages** <100 mV_{pp} at 30 MHz bandwidth <0.96 mV_{rms} Psophometric
- **Output protection:** overvoltage disconnection, restriction of starting current, short circuit protection, overheating protection
- **Dimensions:** 128 x 56 x 410 mm
- **Weight:** 2,9 Kg