

## CX-600NC



Coaxial Relay SPDT 1x N, 2x cable, 12VDC

### Cena

Predajná cena bez DPH: 100,76 €

[Opýtajte sa na tento produkt](#)

| Popis produktu | Technical Data        | CX 600 NC                                 |
|----------------|-----------------------|---|
|                | Pull-in voltage       | 10-14 V                                   |
|                | Pull-off voltage      | 3 V DC                                    |
|                | Operating voltage     | 12 V DC at 160 mA/20° C                   |
|                | Pull-in time          | 20 ms typ.                                |
|                | Pull-off time         | 15 ms typ.                                |
|                | Contact type          | 1x UM                                     |
|                | Operating temperature | -50° C - +70° C                           |
|                | Weight                | ca. 230 g                                 |
|                | Installation          | 2 screws, 1 N-socket, 2x cable connection |

| HF characteristics<br>Frequency | VSWR | Isolation | Insertion loss | max. HF power |
|---------------------------------|------|-----------|----------------|---------------|
| 50 MHz                          | 1,03 | 60 dB     | 0,07 dB        | 1000 W        |
| 150 MHz                         | 1,1  | 48 dB     | 0,1 dB         | 1000 W        |
| 500 MHz                         | 1,15 | 37 dB     | 0,15 dB        | 800 W         |
| 1000 MHz                        | 1,2  | 28 dB     | 0,2 dB         | 500 W         |
| 1500 MHz                        | 1,2  | 26 dB     | 0,2 dB         | 350 W         |
| 2000 MHz                        | 1,25 | 23 dB     | 0,23 dB        | 100 W         |