CX540D



Coaxial Relay SPDT 3x BNC, 12VDC

Rating: Not Rated Yet
Price:
Sales price without tax: 115,88 €

Ask a question about this product

Description

MECHANICAL / TERMINAL PROPERTIES	
Contact Material	Gold
Mechanical life (cycles)	10 x 10^6
Electrical life (cycles)	10 x 10^4
Weight	Approx. 200 g
Terminals	Screw terminals
Mounting Position	Any position recommended
ELECTRICAL / TERMINAL PROPERTIES	
Contact Rating	30 W/VDC
Operating Voltage	12 VDC
Voltage drop	Max. 0.1 V / 1 A
Insulation Resistance	Min. 1000 MΩ / 500 VDC
Dielectric Strength	2k volts 50/60 Hz 1 min
CONDITIONS	

Frequency	Loss	Frequency	Loss	Frequency	Loss
MHz	(dB)	MHz	(dB)	MHz	(dB)
0	0.00	1000	0.17	2000	0.25
100	0.05	1100	0.18	2100	0.26
200	0.07	1200	0.19	2200	0.27
300	0.09	1300	0.20	2300	0.28
400	0.11	1400	0.21	2400	0.29
500	0.12	1500	0.22	2500	0.30
600	0.13	1600	0.23	2600	0.31
700	0.14	1700	0.24	2700	0.32
800	0.15	1800	0.25	2800	0.33
900	0.16	1900	0.25	2900	0.34